


TouchONE® Door Access

CFS-1700 Series
Standalone Fingerprint Door Lock



0110000001010111100001110110000100000011111110101010011000000101011110000111011000010000
101100001000000111111110101010011000000101011100001110110000100001110
1011000010000001111111101010100110000001010111000011101100001000011
10110000100000011111111010101001100000010101110000111011000010000110

CFS-1700 Series

Standalone Fingerprint Door Lock

1001100000010101111000011101100001000011
1001100000010101111000011101100001000011

Fingerprint Door Lock, Door Access Controlled by Fingerprint Identification



Main Features

- Fingerprint and/or User Access Code Entry
- UL-listed Latch or Mortise
- Emergency Override Standard Key
- Non-Handed
- Voice Prompt
- Fire-rated & ADA Compliant Lever Handle
- 1:N Identification or 1:1 Verification mode
- 100 Fingerprints or 1,000 Fingerprints (Fingerprint + ID)
- Audit Trail (Data Kit Option) via DB9/USB Connector

Access Versions

- **CFS-1700M** : Commercial UL Listed Mortise
- **CFS-1700C** : Commercial UL Listed Latch
- **CFS-1700R** : Residential UL Listed Latch


Security
and
Convenience

TouchONE®

TouchONE® Door Access

TouchONE® Door Access

CFS-1700 Series
Standalone Fingerprint Door Lock



0110000001010111100001110110000100000011111110101010011000000101011110000111011000010000
10110000100000011111110101010100110000001010111100001110110000100001110
1001100000010101111000011101100001000011
10110000100000011111110101010011000000101011110000111011000010000110
1001100000010101111000011101100001000011
1001100000010101111000011101100001000011

CFS-1700 Series

Standalone Fingerprint Door Lock

Specifications

Item		CFS-1700M	CFS-1700C/R
	Material:	Zinc Alloy Die-Casting	
	Lever Handle	Fire-rated and ADA Compliant	
	Dimensions	1-5/8(D) x 3-1/8(W) x 11-1/8(H) inch	
	Net /Gross Weight	6.9 lbs.	
Electrical:	Voltage	12VDC	
	Battery	1.5V x 8 AA Size Alkaline Battery	
	Battery Life	Longer than 10 months (15 uses per day)	
Fingerprint Identification System	Sensor Type	Optical Lens	
	Enrollment Time	Less than 1 second	
	Verification Time	Less than 1 second	
	Enrollment Method	1:1 Verification, 1:N Identification	
	False Rejection Rate	0.01% or Less	
	False Acceptance Rate	0.001% or Less	
	User Capacity	100 fingerprints or 1,000 fingerprints (Fingerprint + iD)	
Lockset	Lock Type	UL-listed Mortise	UL-listed Latch
	Lock Function	Always Locked from Outside	
	Backset	N/A	2-3/4" / 2-3/8"
	Door Thickness	1-1/2" ~ 2"	
Override	Emergency Override Key	Standard Mechanical Key	
Data Kit Option	Audit Trail:	Download Last 1,000 Events via DB9 Connector	
Features	Non-Handed	Lever can Fit Left or Right Handed Door	
	Voice Prompt	Voice Guidance Messages (Low battery warning included)	
	Automatic Door Lock	Automatic Door Lock after 5 seconds	
		Automatic Lock-out mode upon 5th Unsuccessful Entry Attempts	
	Operating Temperature	-4°F ~ 140°F; -20°C ~ 60°C	
	LED	Blue: Open and Close; Red: Error	

TouchONE® Door Access

Security
and
Convenience

TouchONE®



America's Personal Security Inc
645 Cleveland St., Clearwater, FL 33755
Tel: 727-443-6603 Fax: 954-212-2223
www.apsibiometrics.com
www.americaspersonalsecurity.com